

POCKET GUIDE

Gelmar



Den Braven Sealants

All Round Sealant



A paintable, solvent based plastic elastic sealant and is fungal resistant. Based on synthetic rubbers with good adhesion properties. Used on damp non-porous surfaces. A versatile sealant for sealing joints, repairing small cracks and for bonding. Can be applied even under moist conditions.

Available in cartridges of 280ml
12 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Clear



White

Acryl-W

Acryl-W is a plastic elastic sealant for interior & exterior use, based on acrylic resin emulsion with a good adhesion to many materials. Paintable with emulsion paints, freeze resistant and not corrosive towards metals. Conforms to the SNJF-standard. After curing Acryl-W is weather and rain resistant.



For sealing cracks and joints where moderate amounts of movements can occur (max.12,5%). Not suitable for joints exposed to continuous water immersion. Available in cartridges of 280ml & 4kg pails.
18 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



White



Grey



Beech

Woodflex



Silicone and solvent-free sealant and filler for sealing and joining of parquet, cork, laminate as well as for wooden floors and joinery. Available in 6 different colours suitable on all typical woods. The sealant has excellent adhesion qualities, is fast drying and may be sanded and painted.

Available in cartridges of 300ml
12 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Oak



Beech



Pine



Cherry



Meranti



Imbuia

High Tack is a high quality, strong one component adhesive, with very high grip and tack based on MS Polymer. Instant tack and gluing of panels, skirting boards, windowsills, natural stone, thresholds, mirrors and isolating materials. In coach-work and metal connecting joints. Gluing in shipbuilding industry.

Available in cartridges of 290ml
9 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



White

PU, Applicator & B1 Foam

PU & NBS Applicator Foam B3/ B2 is a one component fast curing construction foam based on moisture curing Polyurethane, containing a safety propellant with excellent gap filling capability. Precise application with the NBS applicator.

For filling joints between walls, ceilings, floors and gaps around pipes, windows and door frames. **B1 Foam** - for filling and sealing cavities between brickwork and insulating of pipeline mountings.

For use with Polyethylene Backing Cord.

PU Foam Cleaner is a cleaner (CFC free) that dissolves uncured PU Foam.

The PU Foam applicator is equipped with a regulator to adjust the foam output. Applicator supplied with an adaptor for the Uni-NBS system.

B1 Foam is a fire retardant, one component polyurethane foam curing by atmospheric moisture up to 180 minute fire retardancy properties.

B3 handheld aerosol canisters of 500ml and 750ml

Gunfoam aerosol canisters of 750ml

Cleaner aerosol canisters of 500ml

Fire Class B1 Fire Retardant available in 700ml

12 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Mirrorfix-MS



Mirrorfix-MS is an adhesive based on SPUR technology. For gluing mirrors. Consult our guide on gluing mirrors.

Available in cartridges of 310ml

9 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



White

Fix-O-Chim



Fix-O-Chim is a fast curing, two component chemical fastener, based on synthetic resins. It is ideal for use instead of plugs or expansion anchors, as no pressure build up takes place. Not recommended for continuous water immersion. Temperature resistance of up to +80°C.

Available in cartridges of 300ml

9 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Grey

Super Glue



Super Glue is a cyano-acrylate based liquid for fast gluing. Super Glue is translucent and provides a very strong bond. Very fast gluing for bonding rubber o-rings, rubber, metals and glass. Also good for bonding in modelling, jewellery and ornaments.

Plastic bottles of 20g & tubes of 3g

9 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Clear

Silicone-1001 Universal

Silicone-1001 Universal is a multi-purpose, ready-to-use silicone sealant, based on acid curing with very good adhesion to many surfaces. Excellent UV and weather resistance. For general use to seal and bond glass, kitchen assemblies and wood.

Available in cartridges of 260ml
18 month shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Clear



White



Black



Grey



Bronze

Aqua Silicone

Aqua-Silicone is a safe, high Shore-A acetoxycuring silicone sealant with very good adhesion on glass. Non-toxic to fish and marine life when fully cured. As a sealant/adhesive in full glass constructions such as aquaria, terraria and glass panels.

Available in cartridges of 300ml
18 months shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Clear



Black

Silicone-NO

Silicone-NO is a high quality neutral curing fungal resistant, durable and elastic sealant with excellent adhesion on many surfaces (without primer). Has good UV and weather resistance. For sealing joints in glazing systems, buildings and general construction industry.

Available in cartridges of 300ml
18 month shelf life In original unopened packaging at temperatures between +5°C and +25°C.



Clear



White



Grey



Bronze



Light Bronze



Beige

Key



Suitable



Limited Suitability



Not Suitable

To be used as a guide line only.
Please contact our office for
detailed info.

Silicone-1001 Universal
Aqua-Silicone
PU & B1 Foam
Silicone-NO
All Round Sealant
Acryl-W
Woodflex
High Tack
Mirrorfix-MS
Fix-O-Chim

Exterior Joints

Facades
Wooden window frames in walls
Metal window frames in walls
Roof joints between bitumen materials
Natural stone, marble, granite
Coach, caravan and containers
Repairing windscreens
Intalling windscreens
Joints in chimneys, ovens and gaskets
Joints in heaters and open fires

Interior Joints

Stairs and walls
Window systems and walls
Cracks in walls
Ceramic tiles and baths-Sanitary
Refrigerators
Movement joints in walls
Pipe transits through walls
Prefab interior wall and ceiling
Joints or cracks and gutters
Marble and granite joints
Wooden tiles and panelling

Adhesives

Decorative tile and polystyrene
Bonding wood to concrete and brick
Adhesion of cornices to ceilings
Adhesion of mirrors

Glazing

Inside glazing, single glass up to 0.2m
Single and double glass surface +0.2m
Window frames - metal and aluminium
Window frames - wood
Combination with enamel paint
Combination with acrylic paint
Combination with layered glass
Repairs to glazing systems
Construction and repair of aquariums
Flush glazed joints
Vertical skylight joints
Horizontal skylight joints
Glass to glass joints

Product	Suitable	Limited Suitability	Not Suitable
Silicone-1001 Universal	✓		●
Aqua-Silicone	✓	✓	✓
PU & B1 Foam	✓	✓	✓
Silicone-NO	✓	✓	✓
All Round Sealant	✓	✓	✓
Acryl-W	✓	✓	✓
Woodflex	✓	✓	✓
High Tack	✓	✓	✓
Mirrorfix-MS	✓	✓	✓
Fix-O-Chim	✓	✓	✓

Chemical Anchoring	✓	✓	✓
Silicone-1001 Universal	✓	✓	✓
Aqua-Silicone	✓	✓	✓
PU & B1 Foam	✓	✓	✓
Silicone-NO	✓	✓	✓
All Round Sealant	✓	✓	✓
Acryl-W	✓	✓	✓
Woodflex	✓	✓	✓
High Tack	✓	✓	✓
Mirrorfix-MS	✓	✓	✓
Fix-O-Chim	✓	✓	✓

Chemical Anchoring	✓	✓	✓
Silicone-1001 Universal	✓	✓	✓
Aqua-Silicone	✓	✓	✓
PU & B1 Foam	✓	✓	✓
Silicone-NO	✓	✓	✓
All Round Sealant	✓	✓	✓
Acryl-W	✓	✓	✓
Woodflex	✓	✓	✓
High Tack	✓	✓	✓
Mirrorfix-MS	✓	✓	✓
Fix-O-Chim	✓	✓	✓

Chemical Anchoring	✓	✓	✓
Silicone-1001 Universal	✓	✓	✓
Aqua-Silicone	✓	✓	✓
PU & B1 Foam	✓	✓	✓
Silicone-NO	✓	✓	✓
All Round Sealant	✓	✓	✓
Acryl-W	✓	✓	✓
Woodflex	✓	✓	✓
High Tack	✓	✓	✓
Mirrorfix-MS	✓	✓	✓
Fix-O-Chim	✓	✓	✓



Den Braven Sealants