

UNIVERSAL STAIN

COLOUR RANGE

DARK OAK

WALNUT

DARK MAHOGANY

DARK BROWN

ANTHRACITE

MAHOGANY

Wood Masters

INTERIOR WOODWORK • GREAT VALUE • EXCELLENT FINISHES



Exclusive to Gelmar

Wood has a natural beauty that is enhanced by the use of our range of stains which emphasize grain and colour, clear sealer for wood protection and hybrid finish lacquer for hard, scratch and water mark resistant coverage giving years of blemish free service.

Surface Preparation is important to help you achieve best professional results. The wood surface must be clean, dry and free from dirt, wax, or grease.

Application & Clean-up

Shake can well before each use. Always hold aerosol can in vertical upright position. Hold can 25cm away from substrate while spraying. To avoid blocking after each use, invert can & spray for approximately 2 seconds checking that only gas is being emitted.



UNIVERSAL STAIN

AEROSOL • SOLVENT BASED •
RICH DEEP COLOUR • PENETRATING

Wood Masters Universal Wood Stain is a high quality, solvent based wood stain which applies easily and enhances the wood's natural grain with its intensified depth of color and clarity. Experience optimal results on all interior wood surfaces such as cabinets, doors, furniture, legs and woodwork. Sand the wood thoroughly, first with a medium grit sandpaper, then progress to a fine grit paper. Always sand in the direction of the wood grain. Sand smooth, then remove dust particles with a lint-free rag or a tack rag.



SANDING SEALER

AEROSOL • EASY APPLICATION
• EXCELLENT SANDING PROPERTIES •

Wood Masters Sanding Sealer is recommended for use on interior wood surfaces as a sandable basecoat or sealer prior to the application of a clear topcoat finish. It may be applied to all types of bare or stained woods. After spraying the surface using the Sanding Sealer, allow 20 minutes for drying. Sand lightly with a fine sandpaper.



FINISHING LACQUER

AEROSOL • QUICK DRY • GOOD BUILD • LOW ODOUR

Wood Masters Finishing Lacquer is a crystal clear, fast-drying interior lacquer that provides a durable finish resistant to water and alcohol. This is a single pack, pre catalysed wood lacquer, based on Acid Catalysed and Nitro Cellulose Technology. Allow 20 minutes to dry (dependent on ambient conditions). A second coat can be applied for optimum quality and durability. Sand the wood thoroughly, first with a medium grit sandpaper, then progress to a fine grit paper.