



# TECHNICAL DATA SHEET: PUTTY & ADHESIVES



## POXY BOND

MULTI-PURPOSE EPOXY ADHESIVE

### FEATURES AND BENEFITS

- Compatible with bricks, concrete, metal, plaster, wood and ceramics
- Easy to use and wipes smooth with water
- 2 pack rapid curing anchor adhesive



### DIRECTIONS FOR USE

### USAGE PRECAUTIONS

Read all instructions before use. Only apply to dry surfaces with a moisture content less than 10%. Do not apply to any damp, contaminated or unsound surface as this will affect the adhesion and performance. Substrate temperature must be between 5 and 30°C. Only mix required amount to avoid wasting product. Contact our product support line on 072 396 4980 for assistance prior to use. Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860254620 for disposal information.

### SURFACE PREPARATION

Remove all loose / flaking material. Sand paper any smooth / glossy surfaces. Thoroughly clean any surface contaminates with Powafix Sugar Soap\* and Powafix Fungi Fix\*.

### APPLICATION INSTRUCTIONS

Mix 1 part A – activator WHITE to 1 part B – base GREY. Use separate scrapers to avoid contaminating the two parts. Mix the two parts together with a clean scraper until colour is uniformly LIGHT GREY and both parts are thoroughly mixed. Use a scraper to apply product. Immediately smooth off with water. Remove excess product from tools and immediately clean with Powafix Eco Powa Brush Cleaner.

Pot life 45 minutes - Touch dry 4 hours – Handle strength 6-8 hours – Full cure 4 – 7 days

**Suitable for bonding:** Steel, Plastic, Fibre Cement, Glass, Concrete/ Brick, Aluminium and Wood.



More than just a product.

BRAND



QUALITY




SERVICE



VALUE



# TECHNICAL DATA SHEET: PUTTY & ADHESIVES



## STORAGE INSTRUCTIONS

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860254620 for disposal information.

## SAFETY INSTRUCTIONS



May cause serious eye damage use protective glasses.



Use protective glasses. Use protective gloves. If medical advice is need have product and packaging at hand.



May cause skin damage and allergic reaction.

If medical advice is need have product and packaging at hand. **IF IN EYES** flush open eyes with plenty water and seek immediate medical attention. **IF SWALLOWED** do not induce vomiting and seek immediate medical attention. **IF ON SKIN** wash with soap and water. Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National Poison centre 0861 555 777

## PRODUCT GUARANTEE


In the unlikely event you are not totally satisfied – this product has a 12 month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned unaltered, in its original packaging with proof of purchase. This warranty excludes product failure caused by misuse of product outside of recommended uses and instructions on the packaging.



# TECHNICAL DATA SHEET: PUTTY & ADHESIVES



## PRODUCT INFORMATION

Barcode	Product Code	Pack Size	Pack Size	
6009600999756	PXBD250ML	125ml + 125ml (Total 250ml)	2	
6009600999763	PXBD500ML	250ml + 250ml (Total 500ml)	2	

## PRODUCT SPECIFICATION

Appearance	A – White paste , B- Grey paste
Density	A – 1.41, B – 1.65

ISSUE DATE: NOVEMBER 2023

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.