



## **ALL PURPOSE CRACK FILLER**

### **DESCRIPTION:**

*Powafix All Purpose Crack Filler is a tough filler formulated with a unique blend of cement and plaster to provide a weather resistant, quick setting and flexible surface for both interior and exterior applications.*

### **RECOMMENDED USES:**

- Fills in gaps around timber or metal door and window frames, skirting boards etc.
- Can be applied to the surface of both interior and exterior cement walls, plaster, gypsum boards and asbestos cement surfaces.
- Can be used to plaster over small surface imperfections.

### **FEATURES & BENEFITS:**

- Quick setting.
- Extra strong adhesion.

### **DIRECTIONS FOR USE:**

1. Open up all cracks to ensure good adhesion. Surfaces to be filled must be clean and dust free.
2. Cover nails and screws with Powafix Metal Primer to prevent rusting or use a universal undercoat.
3. Add 2 parts All Purpose Crack filler to 1 part water & mix thoroughly. Allow to stand 5 min before using.
4. Stir well to smooth paste. Crack Filler remains workable for about 1 hour after mixing.
5. Press paste into cavities with putty knife or trowel. Deep cavities can be filled in two or more stages. Drying time 2-4 hours.
6. Sand smooth with a medium grit sand paper. Prime repaired area with Powafix Water Repellent or Powafix Tradeshield Plaster Primer.



### SAFETY INSTRUCTIONS

#### READ INSTRUCTIONS BEFORE USE



Use within well-ventilated areas. Wear a dust mask. Do not inhale dust.



Use protective glasses. If contact with eyes occurs, flush open eyes with plenty of water and seek immediate medical attention.



Wear protective gloves. Avoid contact with skin. If contact with skin occurs, wash with soapy water.



Store out of reach of children and animals. If swallowed do not induce vomiting and seek immediate medical attention.



This product contains cement which is a potential irritant to the eyes, skin & respiratory tract.

**Poison Info. Line: 021 689 5227 / 0861 555 777**



### GALLERY:

		
<p>500G Box 10 per case CFAP500G 6009600990005</p>	<p>2KG Box 10 per case CFAP2KG 6009600990012</p>	<p>10KG Bag Each CFAP10KG 6009600990029</p>

### COLOUR:

- Off white powder.

### ASSOCIATED PRODUCTS:

- Universal Undercoat.
- Powafix Water Repellent.
- Powafix Sugar Soap.
- Plaster Primer.
- Metal Primer

### SPECIFIC DATA:

APPEARANCE:	UNIFORM FINE POWDER.
SG@23°C:	N/A
APPLICATION TEMP:	8°C → 35°C
OPEN TIME:	1 HOUR
MAXIMUM APPLICATION:	10 – 15 mm
SHELF LIFE:	MINIMUM 12 MONTHS WHEN STORED TO MANUFACTURERS RECOMMENDATIONS.
DRYING TIME:	4 – 6 HOURS

CODE & ISSUE DATE:

CFAP JAN 2017

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.