

Ref: Q/JL SX01P03-202001

General Spray Paint

NA-0006A

No.: TDS25NA120EN0000

Revision Date: 2025-09-04

Issue Date: 2025-09-04

PRODUCT DESCRIPTION

1. General Spray Paint is a quick-dried acrylic aerosol paint, with convenient application, perfect atomization and high emission rate
2. General Spray Paint film has high plumpness, excellent adhesion performance and rich colors, perfect decoration and protection functions.
3. General Spray Paint is widely used for surface-maintenance of metal, wood, plastic materials, etc.

TYPICAL APPLICATIONS

1. It is widely used in metal, wood, glass, leather goods, ceramics, ABS plastic and other material objects of the spraying or mending.
2. It is suitable for the surface of vehicle, machinery, dashboard, home appliance and other metal, the wood with treated surface, glass, ABS plastic.
3. It is used for the spray and maintenance of various substrate.

FEATURE

1. Fast dry
2. High Coverage
3. Excellent weather resistance
4. Toluene-free
5. Lead-free

TECHNICAL FEATURES

Items	C*a/T*b/S*c/O*d	Unit	Typical Value	Requirement	Test Std	Eqv. Std
Appearance		/	/	Glossy & Even	Q/JL-00-T001	
Tack free	///Finger	min	5	≤15	GB/T 1728	
Drying Time	///Filter Paper	min	15	≤60	GB/T 1728	
Leak Test		/	/	No leakage	QB 2549-2002	
Water Resistance	///Water Immersion	/	/	No visible change	GB/T 1733	ГОСТ 9.403:1980

Notes: *a, Conditioning, specimen is conditioned under (23±2) °C, (50±5)% relative humidity if not specified;

*c, Substrate

*b, Testing Condition, specimen is tested at (23±2) °C, (50±5)% relative humidity if not specified;

*d, Others need to be specified.

The above data is intended to provide guidance for use and should not be used to write product specifications

DIRECTIONS FOR USE

APPLICATION TEMPERATURE: +5°C to +45°C

1. Clean the object-surface thoroughly, removing all the dirt, grease, oil, wax, rust, moisture etc. Cover adjacent areas to protect from spray mist.
2. Shake the can vigorously for about 30 seconds before spraying.
3. Hold the can 15-25cm away from the object-surface, press the spray button firmly with steady even strokes while moving the can rapidly back and forth
4. Two or three layers of films with 20-30um are better. Intermittence of 10 minutes between each film is recommended.
5. Before painting is stored, make it upside-down then press the spray button for 3 seconds and wash off surplus paint around the outlet.

RESTRICTIONS

1. Do not use in Confined Spaces. Provide adequate ventilation.
2. Do not smoke while using this product. Stay away from fire.

STORAGE AND SHELF LIFE

36 months in unopened packaging in a cool and dry storage place at temperatures between +8 °C and 28 °C, humidity between 30% and 70%. Optimal storage is at the lower half of this temperature range and humidity range.
To prevent contamination of unused product, do not return any material to its original container.

COLOR

Red, Black, White, etc.

Different colours are available.

PACKAGE

Iron Can: 200 mL, 300 mL, 400 mL, etc.

Different packages are available.

SAFETY

Keep out of reach of children. Before operation, please carefully read the specifications of products and material, and instructions on the package of container.

For more information about safety, please refer to the MSDS.

NOTES

Copyright, JOIN LEADER Company. All rights reserved.

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive property of Join Leader. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Join Leader's written consent. The technical information in this document serves as an indication and is non-exhaustive. Join Leader is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Join Leader reserves the right to amend the wording of this document. Join Leader cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document.

The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage.

-----END-----

TDS25NA120EN000
0

The management system has been certified according to ISO 9001:2015, ISO 14001:2015, ISO 45001:2018.

Page 2/2

JOINLEADER® is a trademark of SAINT-GOBAIN JOINLEADER
(HANGZHOU) NEW MATERIALS CO., LTD.

Email: Freesia.Wang@Saint-Gobain.cn

Web: www.saint-gobain.com.cn/ www.joinleader.cn/ www.tekbond.com

