According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

Section 1 -Identification: Product identifier and chemical identity

·1.1 Product identifier

·Trade name: SILICONE SPRAY

·1.2 Relevant identified uses of the substance or mixture and uses advised against application of the substance / the mixture Lacquer

A aerosol product for water displacement

·1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ARISTO INDUSTRIES CORP. LTD.

XIAOXIANG INDUSTRIAL AREA, WANJIANG TOWN, DONGGUAN, GUANGDONG, CHINA

Tele-Nr. (++86)- 755-22214189 Fax-Nr. (++86)- 755-22214186

•1.4 Emergency telephone number: +86-755-22214189

Section 2 - Hazard identification

- ·2.1 Classification of the substance or mixture
- ·Classification according to Regulation (EC) No 487/2013



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Flam. Aerosol 1 H229: Pressurised container: May burst if heated



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.



GHS08

Asp. Tox. 1: H304 May be fatal if swallowed and enters airways



GHS09

Aquatic Acute 1: H400 Very toxic to aquatic life

Aquatic Chronic 1:H410 Very toxic to aquatic life with long lasting effects

·Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

·Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

·2.2 Label elements

·Labeling according to Regulation (EC) No 487/2013

The product is classified and labeled according to the CLP regulation.

·Hazard pictograms









GHS02 GHS07 GHS08

Signal word Danger
 Hazard-determining components of labeling:

No Data Available

·Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

·Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray..

P270 Do not eat, drink or smoke when using this product.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

·Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

·2.3 Other hazards

·Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

INGREDIENTS	Annex VI Index Number	CAS NO INDEX	ENIECS	Classification	WT(%)
Dimethyl Ether	603-019-00-8	115-10-6	204-065-8	Flam. Gas 1:H220	30~40
n-Heptane	601-008-00-2	142-82-5	205-563-8	Flam. Liq. 2: H225; Asp.Tox.1:	40~50
				H304; Skin Irrit. 2: H315;	
				STOT SE 3: H336; Aquatic	
				Acute 1: H400; Aquatic	
				Chronic 1:H410	
Simethicone	N/A	8050-81-5	617-098-1	Eye Irrit. 2:H319; Aquatic	10~20
				Chronic 3: H412	

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

· Additional information:

For the wording of the listed risk phrases refer to section 16.

Section 4 – First aid measures

·4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Section 5 - Fire-fighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water spray(large fires only), foam, dry chemical or carbon dioxide.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

Section 6 - Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storages

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packaging with pressurized containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- 7.3 Specific end use(s) No further relevant information available.

Section 8 - Exposure controls and personal protection

· 8.1 Control parameters

No information.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Otherwise, filter class A / P2 or self contained.

· Protection of hands:

Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.

KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

degradation

· Material of gloves Butyl rubber, BR

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

· Eye protection: Safety glasses

Section 9 - Physical and chemical properties

Appearance: Viscous liquid
Odour: Solvent

Odour threshold: Not determined pH: Not determined

Self-igniting Product is not self-igniting.

Melting point/freezing point: <-20°C

Boiling point: >60°C

Not determined Flash point: **Evaporation rate:** Not determined Flammability (solid, gas): Flammable Upper/lower flammability or explosive limits: Not determined Not determined Vapour pressure: Vapour density: Not determined 0.93~0.95g/cm³ Relative density: Vapour density Not determined

Solubility: Not water soluble. Re-dispersible in aromatic

solvents or ketones.

Auto-ignition temperature:Not determinedDecomposition temperature:Not determinedViscosity:Not determinedExplosive properties:Not determinedOxidising properties:Not determinedPartition coefficient (n-octanol/water)Not determined

Section 10 - Stability and reactivity

- 10.1 Reactivity: Stable under recommended storage and handling conditions.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions: No dangerous reactions known.
- · 10.4 Conditions to avoid: No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

Section 11 - Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

No information.

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eve: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful, Irritant, Vapours have narcotic effect.

Section 12 - Ecological information

· 12.1 Toxicity

No information.

12.2 Persistence and degradability

No information.

· 12.3 Bioaccumulative potential

No information.

- · 12.4 Mobility in soil Very slow
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

Section 13 - Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue			
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances		
15 01 04	metallic packaging		
15 01 11*	metallic packaging containing a dangerous solid porous matrix		
	(for example asbestos), including empty pressure containers		

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

Section 14 - Transport information

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
· ADR	UN1950 AEROSOLS	
· IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
· ADR		
· Class	2 5F Gases.	
·Lable		
· IMDG, IATA	2.1	
· Class		
·Lable		
Edulic	2.1	
3	2.1	
· 14.4 Packing group		
· ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Gases.	
· Danger code (Kemler): -	-	
· EMS Number:	F-D,S-U	
• 14.7 Transport in bulk according to Annex II of MARPOL73/78 and		
the IBC Code	Not applicable.	
· Transport/Additional information:		
· ADR	41	
· Limited quantities (LQ)	1L Code 50	
· Excepted quantities (EQ)	Code: E0	
· Transport category	Not permitted as Excepted Quantity 2	
· Tunnel restriction code	D D	
· IMDG		
· Limited quantities (LQ)	1L	
• Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1	
OH MONCH REGULATION .	0141030, ALNO30L3, 2.1	

Section 15 - Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Section 16 - Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

According to NO. 487/2013/EC

Printing Date: 28.07.2019 Version Number 4 Revision date: 25/11/2021

· Relevant phrases

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray..

P270 Do not eat, drink or smoke when using this product.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Contact: Dipl.-Chem. G. Heller oder Dipl.-Ing. U. Voetter

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1